

MAINTENANCE

ITEM	QTY	DESIGNATION	PART N°	
			Standard	High Temp
Ball seals kit:			11 14 01 93 00	11 14 01 96 00
10	1	Ball seal (PTFE / PEEK)	11 14 01 00 01	11 14 22 00 01
12	1	Main seal (PTFE / PEEK)	11 14 01 00 04	11 14 22 00 02
Ball kit:			11 14 01 94 00	
11	1	Ball (316)	12 96 06 00 09	
Handle kit:			11 14 01 91 00	on request
1	1	Screw M6x20 (st st)	-	
2	1	Washer W6 (st st)	-	
3	1	Handle (st st)	11 14 01 10 03	
4	1	Bearing (PTFE / PEEK)	12 96 06 00 13	11 14 22 00 04
5	1	O'ring (Viton)	70 10 03 02 08	
6	1	Spacer (PTFE / PEEK)	11 14 02 00 03	11 14 22 00 03
7	1 / 2	O'ring (FEP+Silicon / PFA+Silicon)	70 10 15 00 66	70 10 17 00 38
8	1	Spindle Gasket (PTFE / PEEK)	11 14 02 00 01	11 14 22 00 05
9	1	Spindle (st st)	11 14 02 00 02	
Spindle seals kit:			11 14 01 92 00	on request
4	1	Bearing (PTFE / PEEK)	12 96 06 00 13	11 14 22 00 04
5	1	O'ring (Viton)	70 10 03 02 08	
6	1	Spacer (PTFE / PEEK)	11 14 02 00 03	11 14 22 00 03
7	1 / 2	O'ring (FEP+Silicon / PFA+Silicon)	70 10 15 00 66	70 10 17 00 38
8	1	Spindle Gasket (PTFE / PEEK)	11 14 02 00 01	11 14 22 00 05
Filter kit:			11 14 01 95 00	
13	1	Filter (st st)	-	
14	1	Lock Ring (st st)	-	
1 1/2" BSP Cap kit:			11 14 01 30 00	
15	1	Cap Seal	12 85 97 00 10	
16	1	BSP Cap & Chain	-	
Tools kit:			11 14 01 90 00	
A	1	Spindle stop tool (Alu 2017T4)	11 14 01 90 01	
B	1	Spindle seal tool (st st)	11 14 01 90 02	

Nb Perolo recommends :

- The spindle seals should be changed simultaneously to maintain the ball valve spindle perfectly tight.
- Both ball gaskets should be changed simultaneously.
- Material of the parts are indicated for Stainless Steel Version. It may vary in HALAR Coated version. Please refer to HIGH CORROSION Catalogue for more details

